

Hongshang

H-2F

Thin-wall heat shrink tubing / flexible / flame retardant / 2:1 / mil spec 135 degrees

Features:

- Crosslinked Polyolefin
- Shrink ratio: 2:1
- Flame retardant
- High flexibility

Approvals:

- UL224 125 °C VW-1 600 V file E204071
- CSA file no.: 1934614
- Meets: RoHS, Sony-SS-00259
- Meets: SAE-AMS-DTL-23053/5 class 1 and 2

Application:

- Operating temperature: -55 °C to +135 °C
- Minimum shrink temperature: +70 °C
- Minimum full recovery temperature: +100 °C
- Longitudinal change: 0 ± 10% max.

Order information:

- Color: black
- Other colors: red, blue, yellow, green, white (flame retardant class 1, size available up to 76,2 mm). Transparent (class 2, not flame retardant)

Type / Size	As supplied: inside diameter in mm (min)	After recovery: inside diameter in mm (max)	After recovery: wall thickness in mm (min)	Reel / Meter
H-2F 1,2/0,6	1,2	0,6	0,40	150
H-2F 1,6/0,8	1,6	0,8	0,40	150
H-2F 2,4/1,2	2,4	1,2	0,48	150
H-2F 3,2/1,6	3,2	1,6	0,48	150
H-2F 4,8/2,4	4,8	2,4	0,48	75
H-2F 6,4/3,2	6,4	3,2	0,56	75
H-2F 9,5/4,8	9,5	4,8	0,62	75
H-2F 12,7/6,4	12,7	6,4	0,62	50
H-2F 16,0/8,0	16,0	8,0	0,68	50
H-2F 19,0/9,5	19,0	9,5	0,68	30
H-2F 25,4/12,7	25,4	12,7	0,87	30
H-2F 32,0/16,0	32,0	16,0	1,00	30
H-2F 38,1/19,0	38,1	19,0	1,00	30
H-2F 50,8/25,4	50,8	25,4	1,10	30
H-2F 76,2/38,1	76,2	38,1	1,20	15
H-2F 102,0/50,8	102,0	50,8	1,35	15
H-2F 126,0/63,5	126,0	63,5	1,40	15
H-2F 150,0/76,0	150,0	76,0	1,40	15