

Hongshang

H-2F(4X)

Thin-wall heat shrink tubing / flexible / flame retardant / 4:1 / mil spec 135 degrees

Features:

- Crosslinked Polyolefin
- Shrink ratio: 4:1
- Flame retardant
- High flexibility

Approvals:

- UL224 125 °C VW-1 600 V file E204071
- CSA file no.: 1934614
- Meets: RoHS
- Meets: SAE-AMS-DTL-23053/5 class 1 and 2

Application:

- Operating temperature: -55 °C to +135 °C
- Minimum shrink temperature: +70 °C
- Minimum full recovery temperature: +100 °C
- Longitudinal change: 0 ± 10% max.

Order information:

- Color: black

Type / Size	As supplied: inside diameter in mm (min)	After recovery: inside diameter in mm (max)	After recovery: wall thickness in mm (min)	Reel / Meter
H-2F(4X) 19,1/4,6	19,1	4,6	1,7	1220
H-2F(4X) 25,4/7,0	25,4	7,0	1,7	1220
H-2F(4X) 38,1/9,5	38,1	9,5	1,7	1220
H-2F(4X) 50,8/14,0	50,8	14,0	1,7	1220
H-2F(4X) 76,2/20,6	76,2	20,6	1,7	1220
H-2F(4X) 102,0/26,7	102,0	26,7	1,7	1220
H-2F(4X) 115,0/36,8	115,0	36,8	1,7	1220