

Hongshang

H-200E and H-200E(TW)

Special heat shrink tubing / Viton® / 200 degrees / 2:1

Features:

- H-200E = Fluoroelastomer tubing
- H-200E(TW) = thin-wall Fluoroelastomer tubing
- Crosslinked Fluoroelastomer
- Shrink ratio: 2:1
- Superior abrasion resistance
- High temperature resistance
- Excellent resistance to aggressive chemicals and solvents

Approvals:

- Meets: RoHS
- Meets: SAE-AMS-DTL-23053/13

Application:

- Operating temperature: -55 °C to +200 °C
- Minimum full recovery temperature: +175 °C
- Longitudinal change: 0 ± 10% max.

Order information:

- Color: black
- Available in various wall thicknesses

Type / Size	As supplied: inside diameter in mm (min)	After recovery: inside diameter in mm (max)	After recovery: wall thickness in mm (min)	Reel / Meter
H-200E 3,2/1,6	3,2	1,6	0,76	50
H-200E 4,8/2,4	4,8	2,4	0,9	50
H-200E 6,4/3,2	6,4	3,2	0,9	50
H-200E 9,5/4,8	9,5	4,8	0,9	50
H-200E 12,7/6,4	12,7	6,4	1,1	30
H-200E 19,0/9,5	19	9,5	1,3	30
H-200E 25,4/12,7	25,4	12,7	1,65	30
H-200E(TW) 9,5/4,8	9,5	4,8	0,9	50
H-200E(TW) 12,7/6,4	12,7	6,4	0,9	30
H-200E(TW) 15,9/7,9	15,9	7,9	1,07	30
H-200E(TW) 19,1/9,5	19	9,5	1,07	30
H-200E(TW) 22,0/11,0	22	11	1,25	30
H-200E(TW) 25,4/12,7	25,4	12,7	1,25	30
H-200E(TW) 31,8/15,7	31,8	15,7	1,4	30