

Hongshang

HRTM

Medium-wall heat shrink tubing / with hot melt adhesive (co-extrusion)

Features:

- Medium-wall tubing with hot melt adhesive
- Co-extrusion technology
- Good electrical and mechanical performance
- Ideal for low voltage applications
- UV resistant

Approvals:

- Meets: RoHS

Application:

- Operating temperature: -55 °C to +110 °C
- Minimum full recovery temperature: +120 °C
- Longitudinal change: 0 ± 10% max.

Order information:

- Also available in lengths of 1 and 1,5 meter
- Color: black

Type / Size	As supplied: inside diameter in mm (min)	After recovery: inside diameter in mm (max)	After recovery: wall thickness in mm (min)	Standard length in mm
HRTM 8/2	8,0	2,0	1,4	1220
HRTM 12/3	12,0	3,0	1,4	1220
HRTM 16/5	16,0	5,0	1,5	1220
HRTM 22/6	22,0	6,0	2,0	1220
HRTM 33/8	33,0	8,0	2,0	1220
HRTM 40/12	40,0	12,0	2,0	1220
HRTM 55/16	55,0	16,0	2,0	1220
HRTM 65/19	65,0	19,0	2,5	1220
HRTM 75/22	75,0	22,0	2,7	1220
HRTM 85/25	85,0	25,0	2,8	1220
HRTM 95/25	95,0	25,0	2,8	1220
HRTM 115/34	115,0	34,0	3,4	1220
HRTM 140/42	140,0	42,0	3,4	1220
HRTM 160/50	160,0	50,0	3,4	1220