

Hongshang

HRTH

Heavy-wall heat shrink tubing / with hot melt adhesive (co-extrusion)

Features:

- Heavy-wall tubing with hot melt adhesive
- Co-extrusion technology
- Excellent electrical and mechanical performance
- UV resistant

Approvals:

- Meets: RoHS

Application:

- Operating temperature: -55 °C to +110 °C
- Minimum full recovery temperature: +120 °C
- Longitudinal change: 0 ± 10% max.

Order information:

- Also available in lengths of 1 and 1,5 meter
- Color: black

Type / Size	As supplied: inside diameter in mm (min)	After recovery: inside diameter in mm (max)	After recovery: wall thickness in mm (min)	Standard length in mm
HRTH 9/3	9,0	3,0	1,95	1220
HRTH 15/4	15,0	4,0	2,35	1220
HRTH 20/6	20,0	6,0	2,45	1220
HRTH 33/8	33,0	8,0	3,15	1220
HRTH 43/12	43,0	12,0	4,05	1220
HRTH 51/16	51,0	16,0	4,05	1220
HRTH 75/22	75,0	22,0	4,20	1220
HRTH 85/25	85,0	25,0	4,20	1220
HRTH 95/25	95,0	25,0	4,20	1220
HRTH 105/25	105,0	25,0	4,20	1220
HRTH 115/34	115,0	34,0	4,20	1220
HRTH 130/36	130,0	36,0	4,20	1220