

Hongshang

HSEC and HCEC

Moulded parts / cable end caps with spiral adhesive coating

Features:

- HSEC = standard end cap
- HSEC-L = standard end cap, extended length
- HCEC = conductive end cap
- Crosslinked Polyolefin
- Excellent sealing properties
- Ideal for low voltage applications
- UV and weather resistant

Approvals:

- Meets: RoHS

Application:

- Operating temperature: -55 °C to +110 °C
- Minimum full recovery temperature: +120 °C
- Longitudinal change: 0 ± 10% max.

Order information:

- Color: black

Type / Size	As supplied: inside diameter in mm (min)	After recovery: inside diameter in mm (max)	After recovery: wall thickness in mm (min)	After recovery: length in mm
HSEC 105	12,0	4,0	2,6	40,0
HSEC 110	14,0	5,0	2,2	45,0
HSEC 115	20,0	6,0	2,8	55,0
HSEC 120	25,0	8,5	2,8	68,0
HSEC 130	35,0	16,0	3,3	90,0
HSEC 135	40,0	16,0	3,3	83,0
HSEC 140	55,0	26,0	3,5	103,0
HSEC 150	75,0	36,0	4,0	120,0
HSEC 160	100,0	52,0	4,0	140,0
HSEC 170	120,0	60,0	4,0	150,0
HSEC 180	145,0	60,0	4,0	150,0
HSEC 190	160,0	80,0	4,0	150,0
HSEC 110L	14,0	5,0	2,2	55,0
HSEC 130L	40,0	15,0	3,3	90,0
HSEC 140L	55,0	23,0	3,8	140,0
HSEC 145L	62,0	23,0	3,8	140,0
HSEC 150L	75,0	36,0	4,0	150,0
HSEC 150XL	75,0	36,0	4,2	170,0
HSEC 160L	100,0	47,0	4,0	155,0
HCEC 120	25,0	8,5	2,8	68,0
HCEC 130	42,0	15,0	3,3	110,0
HCEC 140	55,0	23,0	3,8	140,0
HCEC 145	62,0	23,0	3,8	140,0
HCEC 150	75,0	32,0	4,0	150,0
HCEC 150L	75,0	36,0	4,2	170,0
HCEC 160	105,0	45,0	4,0	150,0